Fire truck AZ 4,0-40 (URAL 43206-79)

Fire truck AZ 4,0-40 (URAL 43206-79) intended for:

- delivery to the fire site of fire personnel, fire extinguishing substances, fire-technical equipment (FTE) and rescue equipment (RE),
- extinguishing fires and emergency rescue operations, using a fire truck, fire personnel, fire extinguishing, substances, FTE and RE.



Capacity volume for water, I		from 0 to 4000
Capacity volume for frother, I		240 (other as per customer request)
Overall dimensions (length / height / width), mm		8200x3310x2500
Full mass, kg		13100
Colorography schemes		GOST R 50574-2002 (other as per customer request)
all-metal standard chassis cabin, two-door, single-row, two places		
water tank, foam tank, fire pump, water and foam communications,		
body superstructure with compartments for fire-technical equipment and rescue equipment		
normal pressure centrifugal fire pump NZPN-40/100, (according to GOST R 52283-2004 "Centrifugal fire pumps. General technical requirements. Test methods"), rear location (other as per customer request)		
from 0 to 40 liters per second (or another with another fire pump)		
according to the standards of the Order of the Ministry of Emergency Situations of Russia №425 of July 25, 2006 (other as per customer request)		
in the compartments, taking into account the tactics of its operational use, to ensure the reliability of equipment fixation, accessibility, convenience and safety during removal and installation		
3	4 x 4 / all	,
The layout of the base chassis of a fire truck engine layout		front, longitudinal, engine, loading workspace behind cabin
Wheelbase, mm 4405		
Wheel track (front / rear), mm 2040 / 2040		
Engine (type, ecological class) YaMZ-5362		-10, four-stroke, diesel, Euro-5
Engine power, hp 275		
Maximum speed, km/h 90		
Gearbox (type) mechanica		
Tires (type, size) 425/85R		
	all-metal stand water tank, for body superstrand pressure "Centrifugal file rear location (from 0 to 40 lime according to the of July 25, 200 in the compart of equipment is of a fire truck	eight / width), mm all-metal standard chassis c water tank, foam tank, fire p body superstructure with con normal pressure centrifugal "Centrifugal fire pumps. Ger rear location (other as per con according to the standards of of July 25, 2006 (other as per in the compartments, taking of equipment fixation, acces in the compartments, taking of a fire truck engine layout cabin behind 4405 2040 / 2040 YaMZ-53623 275

