## Fire truck AZ 5,0-60 (KAMAZ 43118RF)

Fire truck AZ 5,0-60 (KAMAZ 43118RF) intended for:

- delivery to the fire site of fire personnel, fire extinguishing substances, fire-technical equipment (FTE) and rescue equipment (RE),
- extinguishing fires and emergency rescue operations, using a fire truck, fire personnel, fire extinguishing, substances, FTE and RE.



| Capacity volume for water, I   |   |             | from 0 to 5000  |
|--|---|-------------|---|
| Capacity volume for frother, I   |   |             | 300 (other as per customer request)                                   |
| Overall dimensions (length / height / width), mm   |   |             | 8460x3320x2500  |
| Full mass, kg  |   |             | 18600   |
| Colorography schemes   |   |             | GOST R 50574-2002 (other as per customer request)                     |
| Cab fire truck, the number of places for firefighting crew (including the driver's seat) | four-door cab, six places;<br>cab front - all-metal standard chassis cabin, two-door, two places<br>cab rear - frame-panel type, four-seater;<br>both parts of the cabin form a common saloon             |             |   |
| Execution option of loading space of the fire truck                                      | water tank, foam tank, fire pump, water and foam communications, body superstructure with compartments for fire-technical equipment and rescue equipment  |             |   |
| Fire pump  | normal pressure centrifugal fire pump NZPN-60/100, (according to GOST R 52283-2004 "Centrifugal fire pumps. General technical requirements. Test methods"), rear location (other as per customer request) |             |   |
| Fire pump performance  | from 0 to 60 liters per second (or another with another fire pump)  |             |   |
| Completeness FTE   | according to the standards of the Order of the Ministry of Emergency Situations of Russia №425 of July 25, 2006 (other as per customer request)   |             |   |
| Placement FTE  | in the compartments, taking into account the tactics of its operational use, to ensure the reliability of equipment fixation, accessibility, convenience and safety during removal and installation       |             |   |
|  |   | 6 x 6 / all | , ,   |
|  |   |             | ut front, longitudinal,<br>the engine, loading workspace behind cabin |
| Wheelbase, mm 3685   |   | 3685+1320   |   |
| Wheel track (front / rear), mm 2050  |   | 2050 / 2050 |   |
| Engine (type, ecological class) Can  |   | Cammins IS  | lle-C340, four-stroke, diesel, Euro-5                                 |
| Engine power, hp   |   | 340         |   |
| Maximum speed, km/h  |   | 90          |   |
| Gearbox (type)   |   | mechanical  |   |
| Tires (type, size)   |   | 425/85R21   |   |



