Fire truck AZ 8,0-40 (KAMAZ 43118)

Fire truck AZ 8,0-40 (KAMAZ 43118) intended for:

- delivery to the fire site of fire personnel, fire extinguishing substances, fire-technical equipment (FTE) and rescue equipment (RE),
- extinguishing fires and emergency rescue operations, using a fire truck, fire personnel, fire extinguishing, substances, FTE and RE.



Capacity volume for water, I		from 0 to 8000
Capacity volume for frother, I		480 (other as per customer request)
Overall dimensions (length / height / width), mm		8460x3320x2500
Full mass, kg		21600
Colorography schemes		GOST R 50574-2002 (other as per customer request)
four-door cab, six places; cab front - all-metal standard chassis cabin, two-door, two places cab rear - frame-panel type, four-seater; both parts of the cabin form a common saloon		
water tank, foam tank, fire pump, water and foam communications, body superstructure with compartments for fire-technical equipment and rescue equipment		
normal pressure centrifugal fire pump NZPN-40/100, (according to GOST R 52283-2004 "Centrifugal fire pumps. General technical requirements. Test methods"), rear location (other as per customer request)		
from 0 to 40 liters per second (or another with another fire pump)		
according to the standards of the Order of the Ministry of Emergency Situations of Russia №425 of July 25, 2006 (other as per customer request)		
in the compartments, taking into account the tactics of its operational use, to ensure the reliability of equipment fixation, accessibility, convenience and safety during removal and installation		
Wheel formula / driving wheels 6 x 6 / all		
The lavell of the back chackle of a fire thick is		t front, longitudinal, the engine, loading workspace behind cabin
Wheelbase, mm 3685+1320		
Wheel track (front / rear), mm 2050 / 2050		
Engine (type, ecological class) KAMAZ 740		705-300, four-stroke, diesel, Euro-5
Engine power, hp 300		
Maximum speed, km/h 90		
Gearbox (type) mechanical		
Tires (type, size) 425/85R2		
	four-door cab, cab front - all-cab rear - fran both parts of t water tank, for body superstr normal pressure location (from 0 to 40 li according to to f July 25, 20 in the compand of equipment so f a fire truck	eight / width), mm four-door cab, six places; cab front - all-metal standard cab rear - frame-panel type, both parts of the cabin form water tank, foam tank, fire p body superstructure with con normal pressure centrifugal "Centrifugal fire pumps. Gen rear location (other as per car from 0 to 40 liters per secon according to the standards of of July 25, 2006 (other as per in the compartments, taking of equipment fixation, access for a fire truck acabin above to 3685+1320 2050 / 2050 KAMAZ 740.3 300 90

